



SDS)

SJ4713

2024-01-26

2024-02-25

4.8

GB/T 16483-2008 GB/T 17519-2013

1.

POLYESTER RESIN

SJ4713

CAS

8

241008

0553-5316333

0553-5316330

SDS

ASJ_SDS@ 126.com

[http //www.shen-jian.com](http://www.shen-jian.com)

0553-5316333

2.

GB 13690-2009 GB 30000-2013

/

GHS

GHS

■

P264

P271

P272

■

P302+P352

P362+P364

■

P410+P403

■

P501

vPvB

/

3. /

/

1

8

4.

/

“ ”(11)

5.

CO₂

/

(MSHA/NIOSH)

6.

“ ”

8

13

7

(8)

30 (86)

8.

EN 14042
GBZ/T 160.1~GBZ/T 160.81-2004
WS/T 52 WS/T 110 A

/

9.

PH

/ ()

()

() 350

[%(v/v)]

(kPa)

(=1)

(=1) 1.2

(g/cm³) 1.2 (23)

600 750 kg/m3

(mg/L)

(mg/L)

() 350

() 350

() 350

VOC

10.

(7)

()

11.

_____ / _____

_____ / _____

12.

_____ / _____ (Koc)

PBT vPvB _____

PBT

vPvB

13.

“ ”

14.

	UN	IMDG	IATA
(UN)	—	—	—
	—	—	—
	—	—	—
/			
	—	—	—

MARPOL 73/78 II IBC

15.

	A	B	C	D	E	F	G	H	I	J	K
A				2015			2015		92		
B			2022				2022		8		

1		ICSC	http://www.ilo.org/dyn/icsc/showcard.home
2			http://www.iarc.fr/
3	OECD		http://www.echemportal.org/echemportal/index?page
4	CAMEO		http://cameochemicals.noaa.gov/search/simple
5	:		http://chem.sis.nlm.nih.gov/chemidplus/chemidlite.jsp
6			http://cfpub.epa.gov/iris/
7			http://www.phmsa.dot.gov/hazmat/library/erg
8	GESTIS-		http://gestis-en.itrust.de/

CAS-		TSCA-	TSCA
PC-STEL-		PC-TWA-	
DNEL-		IARC-	
RPE-		PNEC-	
LC ₅₀ - 50%		LD ₅₀ -50%	
NOEC-		EC ₅₀ -50%	
PBT-		POW-	/
BCF-	(BCF)	vPvB-	
CMR-		IMDG-	
ICAO/IATA-	/	UN-	
ACGIH-		NFPA-	
OECD-			